

## Under-counter POU System for Arsenic, Lead, Cyst, Chlorine, Taste & Odor Reduction

Model No. DWS-2S-2710-01

## AdVantEdge™ Dual System

A multi-functional integrated system system for undercounter household residential use. Features a two-stage treatment approach using selected NSF® 42 listed 10inch (standard size) carbon block cartridge for lead, cyst, chlorine, taste & odor reduction, and a 10-inch arsenic removal cartridge. The system includes housing components i.e., sumps, caps, mounting bracket, faucet (lead-free), shut-off device, and tubing for a complete AdEdge Technologies, Inc. supplies both the system components and replacement cartridges; the system is available to qualified water treatment distributors, dealers and professionals for subsequent resale to end users. Replacement cartridges are available through AdEdge authorized distributors. Retail sales, marketing, distribution, installation and monitoring will be provided by others.



## Specifications: Model # DWS-2S-2710-01

Filtration Cartridge 10-inch standard, 5-micron polypropylene sediment cartridge

Arsenic Cartridge 10-inch standard (2.70 x 9.75-inch); Adedge Model AD2710C or AD2710S

Materials Housing Injection molded plastic

Mounting Painted metal mounting bracket
Faucet Lead-free faucet with ¼ inch tubing

Shut Off Device Mechanical countdown shut-off device mounted on bracket

Arsenic media Adedge custom AD33L product Chlorine, Taste, odor Media Granular activated carbon

Water source Potable water of known microbiological quality (microbiologically safe)
NSF testing Components tested in accordance with NSF protocols, no specific listings

Box/Packaging Plain white box, with or without Label (language TBD)

## **Performance**

Rated Cartridge Life 800 gallons (without shut off device)

Arsenic concentration Up to 50 ppb influent arsenic

Replacement Every 12 months or 800 gallons whichever comes first

Rated flow rate 0.5 gpm

Parameters Odor, taste, chlorine, arsenic

