

DEMAND MODEL NAME	MINERAL CU. FT.	LOW SALT GRAINS/LBS.	CAPACITY MED. SALT GRAINS/LBS.	HIGH SALT GRAINS/LBS.	SERVICE FLOW RATING GPM/PSI	FLOW RATE @ 15 PSI	BACK WASH RATE GPM	MINERAL TANK (INCHES)	BRINE TANK	
									TANK SIZE (INCHES)	SALT STORAGE (POUNDS)
H100-24-BLK	0.75	19,980/6.0	21,040/7.5	24,230/11.5	9.8/10	13.1	1.3	8 x 44	18 x 33	360
H100-32-BLK	1	26,650/8.0	28,060/10.0	32,310/15.0	10.1/10	13.0	1.7	9 x 48	18 x 33	360
H100-32-10-BLK	1	26,650/8.0	28,060/10.0	32,310/15.0	11.3/10	14.5	2.2	10 x 44	18 x 33	360
H100-48-BLK	1.5	39,970/12.0	42,090/15.0	48,460/22.5	10.5/10	14.1	2.2	10 x 54	18 x 40	360
H100-64	2	53,300/16.0	56,120/20.0	64,620/30.0	14.2/10	18.2	4.2	13 x 54	18 x 40	360
H100-96	3	79,950/24.0	84,180/30.0	96,930/45.0	14.4/10	19.2	4.2	14 x 65	24 x 41	660
H100-128	4	106,600/32.0	112,240/40.0	129,240/60.0	15.1/10	20.1	5.3	16 x 65	24 x 41	660
H100-160	5	133,250/40.0	140,300/50.0	161,550/75.0	17.3/10	22.7	7.5	18 x 65	24 x 50	825
H100-192	6	159,900/48.0	168,360/60.0	193,860/90.0	17.8/10	23.1	7.5	20 x 62	24 x 50	825