

# PureWaterCooler™

by VERTEX

## Low Cost Hot & Cold water Dispenser

*Economic hot & cold water cooler with filtration makes great tasting water from your tap. Eliminates the hassle of 5-gallon bottles. Great for offices and factories.*

### Features

- Two temperature system  
Cold: 37-50° F, Adjustable • Hot: 180° F, Autocontrol  
LED indicator for hot or cold water on the front panel
- Individual on/off control switches for cold or hot water on rear panel
- Completely sealed stainless steel cold reservoir and hot tank
- Convenient, enclosed, no-drip dispensing faucets
- Safety lock for hot water faucet
- Built-in filtration system is easily accessed for replacement  
Available with Reverse Osmosis filtration system  
Or Standard Dual-Cartridge filtration system
- Available with ultraviolet or ozone sterilizer
- Models with refrigeration compartment



Refrigerator option (far left).

Filter assembly is front door accessible (left).

Executive Gray cabinet available (right).



### ORDERING INFORMATION

2-Temp Model - 50 GPD Reverse Osmosis	<b>PWC-1000R</b>
2-Temp Model - Standard Filtration	<b>PWC-1000F</b>
Model with Refrigerator compartment*	<b>PWC-1000RF/FP</b>
Executive Gray Cabinet	add / <b>EG</b>
2-temp model with UV sterilizer	add / <b>UV</b>
2-temp model with Ozone sanitizer	add / <b>OZ</b>
Leak detector option	<b>LC-8021</b>
Optional stand, adds 6 inches to height	<b>call factory</b>
Cup holder	<b>call factory</b>
Replacement Filters	
Sediment	<b>IFA-4035</b>
GAC Carbon	<b>IFA-4034</b>
RO membrane, 50 GPD	<b>MA-4203</b>

### Specifications

Shipping Weight: 58 lb.  
Dimension: 13"W x 15"D x 38"H  
Floor to spigot: 28"  
Spigot to Drip Tray: 7.5"  
Cold tank volume 1 gal  
Hot tank volume .5 gal  
Heating Rate: 1.5 gal/hr 180 °F  
Cooling Rate: 1.5 gal/hr 37-50 °F  
Voltage: 115 VAC  
Power Required: 600w max  
Meets Energy Star Requirements



### Filter System

Standard Filter **1000F**  
**Stage 1:** 5 micron Sediment  
**Stage 2:** 10 micron Activated Carbon  
Reverse Osmosis Filter **1000R**  
Above 2 stages plus  
**Stage 3:** 50-GPD RO Membrane  
Automatic tank full control  
Fully assembled  
- connection hardware included  
ADA compliant

\*In white only, with filter-pack option see page 10

Authorized Dealer

